# Appendix A – Zoning Comparison Table

## R1B.AAA Zone - Single and Semi-Detached Dwellings

	HC1-2020	Proposed amendments
Provisions	Section 6 - R1-B Zone	R1-B Zone Exception (for
		Single/Semis)
Permitted Uses	Single Detached Dwelling	Single Detached Dwelling Semi-Detached Dwelling
Min. Lot Area	360 m2 Interior lot;	220 m2 for an interior lot and
Willia Edit / Ilou	412 m2 Corner lot	265 m2 for a corner lot
Min. Lot	12.0 m interior lot;	8.0 m for an interior lot and
Frontage	15.0 m corner lot	10.0 m for a corner lot
Min. Front yard	6.0 m	4.5 metres to the dwelling and
-		6.0 metres to the garage
Min. exterior side yard	4.0 m	2.4 m, except that an attached garage fronting on flankage street shall be 6.0 metres from the lot line on the flankage street
Min. Interior Side yard	1.0 m each side (with attached private garage)	For single detached dwelling: 1.2 metres on one side and 0.6
	3.0m and 1.0 m (with detached garage or parking space accessed via the front yard or a rear lane)	metres on the other side.
		For semi-detached dwelling: 1.2
		metres, and no (0.0 metres)
		interior side yard is required along common lot line.
Min. Rear Yard	7.5 m	7.0 m
Max. Building Height (m)	11 m	NO CHANGE
Min. GFA	65 m2	NO CHANGE
Min.	50 %	That a maximum of 70% of the
Landscaped		front yard may be permitted as
Open Space -		hardscaping. For the purposes of
required front		this by-law, hardscaping shall be considered as finished space
yard		consisting of pavement, concrete,
		patio stones, interlock or other hard surface treatment.
Provision	4.2 Accessory Buildings in Residential Zones	
	No building, or structure which is accessory to any	That notwithstanding Section
	permitted residential use in any zone shall:	4.2.f), an accessory building or
	a) be established on any lot until or unless the main	combination of
	building or use to which it is accessory is established;	buildings is permitted up to a maximum of 10% lot coverage or
	b) exceed a building height of 4.5 metres in the	10 square metres,
	Residential Zones and 6.5 metres in all other zones	whichever is less.
	where the use is permitted;	
	c) occupy any part of a required exterior side yard	
	or required front yard;	

- d) be nearer than 1.0 metres of a lot line within an interior side yard or 1.0 metres of an interior lot line within a front yard;
- e) be nearer than 1.0 metre of an interior lot line within a rear yard except:
- i) in the case of a mutual private garage or a mutual boathouse in the rear yard on a common interior side lot line, no setback is required,
- ii) in the case of a lot line abutting a navigable watercourse, no setback is required for a boathouse, dock, pier or wharf where the boathouse, dock, pier or wharf abuts the watercourse:
- f) occupy more than 10% of the lot area to a maximum of 75 square metres of useable floor area, whichever is lesser, for all accessory buildings or structures together, in the R1, R2, R3, R4, RL residential Zones; 100 square metres of building area on those lots measuring 0.4 hectares or less in all other zones where the use is permitted, and 200 square metres of building area on those lots measuring 0.4 hectares or more in all other zones where the use is permitted. Swimming pools shall not constitute a structure for the purposes of this provision:

#### Section 4.15 – Decks and Unenclosed Porches

- i) A deck or unenclosed porch having a maximum height of 0.3 m above finished grade or less shall be permitted to encroach into any required yard setback without restriction, provided it is located:
- no closer than 1.0 m to the rear or interior side lot
- no closer than 1.5 m to the front or exterior side lot line;
- ii) A deck or unenclosed porch having a maximum height greater than 0.3 m above finished grade shall be permitted to encroach up to 2.0 m into the required rear yard or required exterior side yard, provided it is located no closer than 2.0 m from the exterior or rear lot line. For interior side yards, it may not encroach further than the required side vard setback. For the front yard, the deck may encroach no greater than 1.5 metres.
- iii) No deck shall have a floor higher than the height of the floor of the first storey of the main dwelling on the lot. Anything constructed above the first storey shall be considered a balcony and is regulated under Section 4.20 of this By-law; and
- iv) A deck or unenclosed porch on a sloping rear yard shall be no closer than 1.5 metres from an interior lot line and 5 metres from the rear lot line, at the point where the deck floor reaches or

That notwithstanding Section 4.15 Exemptions from Yard Provisions, a porch may project into any required front yard setback a distance of not more

than 2.0 metres; any required exterior side yard setback a distance of not more than 1.8 metres; and, any required rear yard setback a distance of not more than

2.5 metres.

That notwithstanding Section 4.15 Exemptions from Yard Provisions, a patio or deck above the finished grade may project into any required rear yard setback a distance of not more than 2.5 metres. Any patio or deck constructed in a rear yard is restricted to a maximum size of 3.1 metres by 2.5 metres.

#### Provision

	exceeds a height of 2 metres above the finished surface of the ground.	
	b) Notwithstanding the above, where the rear lot line adjoins a water body or watercourse, a deck or unenclosed porch may project to the limits of any natural hazard land or top-of-bank setback.	
Provision	Section 4.20 – Other Exceptions from Yard Provisions	R1-B Zone Exception
(a)	sills,belt courses, cornices, chimneys, bay windows, pilasters, hydro meters or gas metres may project into any required yard or setbackarea a distance of not more than 0.65 metres;	NO CHANGE
(b)	eaves or gutters for other than an accessory building may project into any required yard or setback area a distance of not more than 0.65 metres	NO CHANGE
(c)	eaves or gutters of an accessory building may project into any required yard or setback area a distance of not more than 0.3 metres	NO CHANGE
(d)	canopies, awnings, or steps may project into any required rear yard, front yard or exterior side yard area a distance of not more than 1.5 metres	NO CHANGE
(e)	balconies may project into any required rear yard, front yard, interior side yard or exterior side yard area a distance of not more than 1.5 metres provided they are no closer than 3.0 metres from a front yard lot line, exterior lot line or interior lot line and 6.0 metres from a rear lot line;	NO CHANGE
(f)	unenclosed accessibility ramps may project into any required yard;	NO CHANGE
(g)	window or wall-mounted furnaces, heat pumps, gas fireplace vents and outdoor free-standing air conditioning units may project into any required rear yard, interior side yard, or exterior side yard a distance of not more than 1.0 metres and provided it is no closer than 6.0 m to a rear lot line or 1.5 m to an interior or exterior lot line;	That an air conditioning unit shall be setback a minimum of 0.6 metres from any side or rear property line. An air conditioning unit is not permitted in any part of a required front yard or front setback.
(h)	steps including landings, above or below grade entrances and staircases may project into any required rear yard, front yard, interior side yard or exterior side yard area a distance of not more than 1.5 metres; and into the front yard not more than 2.0 metres.	Steps/stairs may project into any required front yard or setback a distance of not more than 3.5 metres.
(i)	a stair encroachment of 3 risers, to a maximum of 0.6 metres, may be permitted.	Not Applicable
		That a garage face can extend a maximum of 1 metre in front of a ground floor porch where it meets all other applicable setbacks.

Provision	Section 3 Definition, Section 4.56, Table 4.56 - Sight or Daylight Triangles	
(a)	Any building, structure, sign or use which would obstruct or impair the vision of a vehicle operator, or any fence or vegetation exceeding 1.0 metres in height above finished grade shall be prohibited within any sight (or daylight) triangle. This provision shall not apply to field crops or a wire farm fence.	a) Intersections of Local Roads "SIGHT TRIANGLE" shall mean the triangular space formed by the intersecting street lines of a corner lot and a line drawn from a point on one of the street lines to a point on the other street line, each point being measured 4.5 metres from
(b)	A sight (or daylight) triangle shall be measured back from the point of any at-grade intersection of two or more street lines on a corner lot and a railway right-of-way in accordance with the street classification as identified on Schedule F of the CountyOfficial Plan and Table 4.56:  Table 4.56: Minimum Sight (or Daylight) Triangle Requirements  Street Classification Intersecting Street Minimum Sight Triangle	the point of intersection of the street lines.  b) Intersections of Local Road / Collector Street "SIGHT TRIANGLE" shall mean
(a)	Local Road	the triangular space formed by the intersecting street lines of a corner lot and a line drawn from a point on one of the street lines to a point on the other street line, each point being measured 7.5 metres from the point of intersection of the street lines.
(c)	minimum and a Transportation Study and Traffic Functional Design Study shall be required by the County in order to help determine the roadway requirements	c) That front yard, side yard and rear yard setbacks shall be measured as if the Sight Triangle does not exist.
Provision	Section 5.2.3 – Parking Space Dimensions	
(a)	Every parking space shall be based upon a rectangular shape having a width of 3.0 metres and a depth of 5.8 metres.	The parking space size located within a garage shall have a minimum width of 3.0 metres and have a minimum length of 6.0
(b)	Notwithstanding anything to the contrary, where the length of a parking space is located adjacent to a wall or fence said parking space shall have a width of 3.3 metres and a depth of 5.8 metres.	metres. Stairs, to a maximum of 3 risers or 0.61 metres, shall be permitted to encroach into this parking space.
(c)	A parallel parking spaces shall have a width of 2.7 metres and a depth of 6.5 metres.	
(d)	Angled parking spaces shall be based upon a rectangular shape in accordance with subsection 5.2.3 a).	
(e)	A tandem parking space shall have a width of 3.0 metres and a minimum length of 11 metres.	

## **R4.BBB Zone - Street Townhouses**

	HC1-2020	Proposed amendments
Provisions	Section 6 – R4 Zone	R4 Zone Exception (for Street Townhouses)
Permitted Uses	Street townhouses etc.	Street townhouse
Min. Lot Area	Interior Lot: 156 m2; or 163 m2 with parking access at rear lane	Interior lot – 150 m2 per unit  Corner lot – 210 m2 per unit
	Corner lot: 215 m2 (with attached garage); or 192 m2 (with parking access at rear lane)	Corner for 210 m2 per unit
Min. Lot Frontage	Interior Lot: 5.5 m or 6.0 m per unit (with parking accessed via a rear lane	Interior lot – 5.5 metres per unit
	Corner lot: 8.0 m or 7.5 m per unit (with parking accessed via a rear lane)	Corner lot – 8.0 metres per unit
Min. Front yard	6.0 m (with attached private garage)  3.0 m (where a detached private garage or parking space is accessed via a rear lane)	4.5 metres to the dwelling and 6.0 metres to the garage
Min. exterior side yard	3.0 metres	2.4 m, except that an attached garage fronting on flankage street shall be 6.0 metres from the lot line on the flankage street
Min. Interior Side yard	1.2 m and 0.0 m along common wall	NO CHANGE
Min. Rear Yard	7.5 m 13.5 m (with parking accessed via a rear lane)	6.0 metres
Max. Building Height (m)	11 m	NO CHANGE
Min. GFA	65 m2	NO CHANGE
Min. Landscaped Open Space - required front yard	30 %	That a maximum of 70% of the front yard may be permitted as hardscaping. For the purposes of this by-law, hardscaping shall be considered as finished space consisting of pavement, concrete, patio stones, interlock or other hard surface treatment.
	Definition of Street Townhouse	Notwithstanding the definition of
	"DWELLING, STREET TOWNHOUSE" shall mean a dwelling containing three or more dwelling units with each dwelling unit being divided one from the other by an above grade vertical common wall, and with each dwelling unit fronting onto a street	Notwithstanding the definition of Dwelling, Street Townhouse, the following shall apply: Townhouses shall mean a dwelling house comprising three or more dwelling units with each dwelling unit being divided one from the other by an above grade vertical common wall, a minimum of 10 square metres in area and each dwelling unit having direct

		access to a yard. A maximum of eight
		dwelling units are permitted in a row.
	No building, or structure which is accessory to any permitted residential use in any zone shall: a) be established on any lot until or unless the main building or use to which it is accessory is established; b) exceed a building height of 4.5 metres in the Residential Zones and 6.5 metres in all other zones where the use is permitted; c) occupy any part of a required exterior side yard or required front yard; d) be nearer than 1.0 metres of a lot line within an interior side yard or 1.0 metres of an interior lot line within a front yard; e) be nearer than 1.0 metre of an interior lot line within a rear yard except: i) in the case of a mutual private garage or a mutual boathouse in the rear yard on a common interior side lot line, no setback is required, ii) in the case of a lot line abutting a navigable watercourse, no setback is required for a boathouse, dock, pier or wharf where the boathouse, dock, pier or wharf abuts the watercourse; f) occupy more than 10% of the lot area to a maximum of 75 square metres of useable floor area, whichever is lesser, for all accessory buildings or structures together, in the R1, R2, R3, R4, RL residential Zones; 100 square metres of building area on those lots measuring 0.4 hectares or less in all other zones where the use is permitted, and 200 square metres of building area on those lots measuring 0.4 hectares or more in all other zones where the use is permitted. Swimming	That notwithstanding Section 4.2.f), an accessory building or combination ofbuildings is permitted up to a maximum of 10% lot coverage or 10 square metres, whichever is less.
	pools shall not constitute a structure for the purposes of this provision;	
Provision	Section 4.15 – Decks and Unenclosed Porches	
(a)	i) A deck or unenclosed porch having a maximum height of 0.3 m above finished grade or less shall be permitted to encroach into any required yard setback without restriction, provided it is located: - no closer than 1.0 m to the rear or interior side lot line and - no closer than 1.5 m to the front or exterior side lot line;	That notwithstanding Section 4.15, a porch may project into any required front yard setback a distance of not more than 2.0 metres; any required exterior side yard setback a distance of not more than 1.8 metres; and, any required rear yard setback a distance of not more than 2.5 metres.
	ii) A deck or unenclosed porch having a maximum height greater than 0.3 m above finished grade shall be permitted to encroach up to 2.0 m into the required rear yard or required exterior side yard, provided it is located no closer than 2.0 m from the exterior or rear lot line. For interior side yards, it may not encroach further than the required side	That notwithstanding Section 4.15, a patio or deck above the finished grade may project into any required rear yard setback a distance of not more than 2.5 metres. Any patio or deck constructed in a rear yard is restricted

	yard setback. For the front yard, the deck may encroach no greater than 1.5 metres.	to a maximum size of 3.1 metres by 2.5 metres.
	iii) No deck shall have a floor higher than the height of the floor of the first storey of the main dwelling on the lot. Anything constructed above the first storey shall be considered a balcony and is regulated under Section 4.20 of this By-law; and	
(b)	iv) A deck or unenclosed porch on a sloping rear yard shall be no closer than 1.5 metres from an interior lot line and 5 metres from the rear lot line, at the point where the deck floor reaches or exceeds a height of 2 metres above the finished surface of the ground.	
	Notwithstanding the above, where the rear lot line adjoins a water body or watercourse, a deck or unenclosed porch may project to the limits of any natural hazard land or top-of-bank setback.	
Provision	Section 4.20 - Other Exceptions from Yard Provisions	
(a)	sills,belt courses, cornices, chimneys, bay windows, pilasters, hydro meters or gas metres may project into any required yard or setbackarea a distance of not more than 0.65 metres;	NO CHANGE
(b)	eaves or gutters for other than an accessory building may project into any required yard or setback area a distance of not more than 0.65 metres	NO CHANGE
(c)	eaves or gutters of an accessory building may project into any required yard or setback area a distance of not more than 0.3 metres	NO CHANGE
(d)	canopies, awnings, or steps may project into any required rear yard, front yard or exterior side yard area a distance of not more than 1.5 metres	NO CHANGE
(e)	balconies may project into any required rear yard, front yard, interior side yard or exterior side yard area a distance of not more than 1.5 metres provided they are no closer than 3.0 metres from a front yard lot line, exterior lot line or interior lot line and 6.0 metres from a rear lot line;	NO CHANGE
(f)	unenclosed accessibility ramps may project into any required yard;	NO CHANGE
(g)	window or wall-mounted furnaces, heat pumps, gas fireplace vents and outdoor free-standing air conditioning units may project into any required rear yard, interior side yard, or exterior side yard a distance of not more than 1.0 metres and provided it is no closer than 6.0 m to a rear lot line or 1.5 m to an interior or exterior lot line;	That an air conditioning unit shall be setback a minimum of 0.6 metres from any side or rear property line. An air conditioning unit is not permitted in any part of a required front yard or front setback.

(h)	steps including landings, above or below grade entrances and staircases may project into any required rear yard, front yard, interior side yard or exterior side yard area a distance of not more than 1.5 metres; and into the front yard not more than 2.0 metres.	Steps/stairs may project into any required front yard or setback a distance of not more than 3.5 metres.
(i)	a stair encroachment of 3 risers, to a maximum of 0.6 metres, may be permitted.	Not Applicable
		That a garage face can extend a maximum of 1 metre in front of a ground floor porch where it meets all other applicable setbacks.
Provision	Section 3 Definition, Section 4.56, Table 4.56 - Sight or Daylight Triangles	R4 Zone Exception
(a) (b)	Any building, structure, sign or use which would obstruct or impair the vision of a vehicle operator, or any fence or vegetation exceeding 1.0 metres in height above finished gradeshall be prohibited within any sight (or daylight) triangle. This provision shall not apply to field crops or a wire farm fence.  A sight (or daylight) triangle shall be measured back from the point of any at-grade intersection of two or more street lines on a corner lot and a railway right-of-way in accordance with the street classification as identified on Schedule F of the CountyOfficial Plan and Table 4.56:  Table 4.56: Minimum Sight (or Daylight) Triangle Requirements  Street Classification Intersecting Street Minimum Sight Triangle (nn)  Local Road 3.0  Collector Road 5.0  Arterial Road 8.0  Collector Road 5.0  Arterial Road 8.0  Arterial Road 8.0  Collector Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Collector Road 8.0  Arterial Road 8.0  Collector Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Collector Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Collector Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Collector Road 8.0  Arterial Road 8.0  Collector Road 8.0  Arterial Road 8.0  Arterial Road 8.0  Collector Road 8.0  Arterial Road 8.0  Arterial Road 9.0  Collector Road 9.0  All Streets 15.0	a) Intersections of Local Roads "SIGHT TRIANGLE" shall mean the triangular space formed by the intersecting street lines of a corner lot and a line drawn from a point on one of the street lines to a point on the other street line, each point being measured 4.5 metres from the point of intersection of the street lines.  b) Intersections of Local Road / Collector Street "SIGHT TRIANGLE" shall mean the triangular space formed by the intersecting street lines of a corner lot and a line drawn from a point on one of the street lines to a point on the other street line, each point being measured 7.5 metres from the point of intersection of the street lines.  c) That front yard, side yard and rear yard setbacks shall be measured as if the Sight Triangle does not exist.
Provision	Section 5.2.3 – Parking Space Dimensions	
(a)	Every parking space shall be based upon a rectangular shape having a width of 3.0 metres and a depth of 5.8 metres.	The parking space size located within a garage shall have a minimum width of 3.0 metres and have a minimum length of 6.0 metres. Stairs, to a
(b)	Notwithstanding anything to the contrary, where the length of a parking space is located adjacent to a wall or fence said parking space shall have a width of 3.3 metres and a depth of 5.8 metres.	maximum of 3 risers or 0.61 metres, shall be permitted to encroach into this parking space.

(c)	A parallel parking spaces shall have a width of 2.7 metres and a depth of 6.5 metres.
(d)	Angled parking spaces shall be based upon a rectangular shape in accordance with subsection 5.2.3 a).
(e)	A tandem parking space shall have a width of 3.0 metres and a minimum length of 11 metres.

## R4.CCC Zone - Back-to-Back Townhouses

	HC1-2020	Proposed amendments
Provisions (Per Block)	Section 6 – R4 Zone	R4 Zone Exception (for Back-to- Back Townhouses)
Permitted Uses	Back-to-Back Townhouses	Back-to-Back Townhouses
Min. Lot Area	480 sq. m. per block (Interior) 480 sq. m. per block (Corner)	Interior – 78 square metres per unit Corner – 105 square metres per unit End – 90 square metres per unit
Min. Lot	15.0 m. (Interior)	Interior – 6.0 metres per unit
Frontage	15.0 m. (Corner)	Corner – 9.0 metres per unit End – 7.2 metres per unit
Min. Front yard	6.0 m.	3.0 m. to dwelling; except 6.0 m to attached garage face
Min. exterior side yard	3.0 m.	3.0 m. to dwelling; except that an attached garage fronting on flankage street shall be 6.0 m from flankage street line
Min. Interior Side yard	2.0 m.	1.2 m.; except 0.0 m on a mutual side lot line separating 2 attached townhouse units
Min. Rear Yard	N/A	NO CHANGE
Max. Building Height (m)	11.0 m.	3 storeys
Min. GFA	65 m2	NO CHANGE
Min. Landscaped Open Space - required front yard	20 %	NO CHANGE
	4.2 Accessory Buildings in Residential Zones	
	No building, or structure which is accessory to any permitted residential use in any zone shall:  a) be established on any lot until or unless the main building or use to which it is accessory is established;  b) exceed a building height of 4.5 metres in the Residential Zones and 6.5 metres in all other zones where the use is permitted;	NO CHANGE

- c) occupy any part of a required exterior side yard or required front yard;
- d) be nearer than 1.0 metres of a lot line within an interior side yard or 1.0 metres of an interior lot line within a front yard;
- e) be nearer than 1.0 metre of an interior lot line within a rear yard except:
- i) in the case of a mutual private garage or a mutual boathouse in the rear yard on a common interior side lot line, no setback is required,
- ii) in the case of a lot line abutting a navigable watercourse, no setback is required for a boathouse, dock, pier or wharf where the boathouse, dock, pier or wharf abuts the watercourse:
- f) occupy more than 10% of the lot area to a maximum of 75 square metres of useable floor area, whichever is lesser, for all accessory buildings or structures together, in the R1, R2, R3, R4, RL residential Zones; 100 square metres of building area on those lots measuring 0.4 hectares or less in all other zones where the use is permitted, and 200 square metres of building area on those lots measuring 0.4 hectares or more in all other zones where the use is permitted. Swimming pools shall not constitute a structure for the purposes of this provision:

#### Provision Section 4.15 – Decks and Unenclosed Porches

(a) i) A deck or unenclosed porch having a maximum height of 0.3 m above finished grade or less shall be permitted to encroach into any required yard setback without restriction, provided it is located:

- no closer than 1.0 m to the rear or interior side lot line and

- no closer than 1.5 m to the front or exterior side lot line;
- ii) A deck or unenclosed porch having a maximum height greater than 0.3 m above finished grade shall be permitted to encroach up to 2.0 m into the required rear yard or required exterior side yard, provided it is located no closer than 2.0 m from the exterior or rear lot line. For interior side yards, it may not encroach further than the required side yard setback. For the front yard, the deck may encroach no greater than 1.5 metres.
- iii) No deck shall have a floor higher than the height of the floor of the first storey of the main dwelling on the lot. Anything constructed above the first storey shall be considered a balcony and is regulated under Section 4.20 of this By-law; and
- iv) A deck or unenclosed porch on a sloping rear yard shall be no closer than 1.5 metres from an interior lot line and 5 metres from the rear lot line,

That notwithstanding Section 4.15, a porch may project into any required front yard setback a distance of not more than 2.0 metres; and any required exterior side yard setback a distance of not more than 1.8 metres;

(b)	at the point where the deck floor reaches or exceeds a height of 2 metres above the finished surface of the ground.  Notwithstanding the above, where the rear lot line adjoins a water body or watercourse, a deck or unenclosed porch may project to the limits of any natural hazard land or top-of-bank setback.	
Provision	Section 4.20 - Other Exceptions from Yard Provisions	
(a)	sills,belt courses, cornices, chimneys, bay windows, pilasters, hydro meters or gas metres may project into any required yard or setbackarea a distance of not more than 0.65 metres;	NO CHANGE
(b)	eaves or gutters for other than an accessory building may project into any required yard or setback area a distance of not more than 0.65 metres	NO CHANGE
(c)	eaves or gutters of an accessory building may project into any required yard or setback area a distance of not more than 0.3 metres	NO CHANGE
(d)	canopies, awnings, or steps may project into any required rear yard, front yard or exterior side yard area a distance of not more than 1.5 metres	NO CHANGE
(e)	balconies may project into any required rear yard, front yard, interior side yard or exterior side yard area a distance of not more than 1.5 metres provided they are no closer than 3.0 metres from a front yard lot line, exterior lot line or interior lot line and 6.0 metres from a rear lot line;	NO CHANGE
(f)	unenclosed accessibility ramps may project into any required yard;	NO CHANGE
(g)	window or wall-mounted furnaces, heat pumps, gas fireplace vents and outdoor free-standing air conditioning units may project into any required rear yard, interior side yard, or exterior side yard a distance of not more than 1.0 metres and provided it is no closer than 6.0 m to a rear lot line or 1.5 m to an interior or exterior lot line;	That an air conditioning unit shall be setback a minimum of 0.6 metres from any side property line. An air conditioning unit is not permitted in any part of a required front yard or front setback.
(h)	steps including landings, above or below grade entrances and staircases may project into any required rear yard, front yard, interior side yard or exterior side yard area a distance of not more than 1.5 metres; and into the front yard not more than 2.0 metres.	Steps/stairs may project into any required front yard or setback a distance of not more than 3.5 metres.
(i)	a stair encroachment of 3 risers, to a maximum of 0.6 metres, may be permitted.	Not Applicable
		That a garage face can extend a maximum of 1 metre in front of a

		ground floor porch where it meets all other applicable setbacks.
Provision	Section 3 Definition, Section 4.56, Table 4.56 - Sight or Daylight Triangles	R4 Zone Exception
(a)	Any building, structure, sign or use which would obstruct or impair the vision of a vehicle operator, or any fence or vegetation exceeding 1.0 metres in height above finished grade shall be prohibited within any sight (or daylight) triangle. This provision shall not apply to field crops or a wire farm fence.  A sight (or daylight) triangle shall be measured	a) Intersections of Local Roads "SIGHT TRIANGLE" shall mean the triangular space formed by the intersecting street lines of a corner lot and a line drawn from a point on one of the street lines to a point on the other street line, each point being measured 4.5 metres from the point of intersection of the street
(b)	back from the point of any at-grade intersection of two or more street lines on a corner lot and a railway right-of-way in accordance with the street classification as identified on Schedule F of the CountyOfficial Plan and Table 4.56:  Table 4.56: Minimum Sight (or Daylight) Triangle Requirements  Street Classification Intersecting Street (Institution Intersecting Street Classification (Intersecting Street Classification (Intersecting Street (Institution Intersecting Street (Institution In	lines.  b) Intersections of Local Road / Collector Street "SIGHT TRIANGLE" shall mean the triangular space formed by the intersecting street lines of a corner lot and a line drawn from a point on one of the street lines to a point on the other street line, each point being measured 7.5 metres from the point of intersection of the street lines.  c) That front yard, side yard and rear
(c)	The values in Table 4.56 shall be considered the minimum and a Transportation Study and Traffic Functional Design Study shall be required by the County in order to help determine the roadway requirements	yard setbacks shall be measured as if the Sight Triangle does not exist.
Provision	Section 5.2.3 – Parking Space Dimensions	
(a) (b)	Every parking space shall be based upon a rectangular shape having a width of 3.0 metres and a depth of 5.8 metres.  Notwithstanding anything to the contrary, where	The parking space size located within a garage shall have a minimum width of 3.0 metres and have a minimum length of 6.0 metres. Stairs, to a maximum of 3 risers or 0.61 metres,
	the length of a parking space is located adjacent to a wall or fence said parking space shall have a width of 3.3 metres and a depth of 5.8 metres.	shall be permitted to encroach into this parking space.
(c)	A parallel parking spaces shall have a width of 2.7 metres and a depth of 6.5 metres.	
(d)	Angled parking spaces shall be based upon a rectangular shape in accordance with subsection 5.2.3 a).	
(e)	A tandem parking space shall have a width of 3.0 metres and a minimum length of 11 metres.	

#### **R4.DDD Zone - Medium Density Block 61**

	HC1-2020	Proposed amendments
	Section 6 – R4 Zone	R4 Zone Exception (for Medium Density Block)
Permitted Uses	Street townhouses, Group townhouses, Stacked townhouses, Back-to-back townhouses	Same, except additional permitted uses: single-detached dwellings and semi-detached dwellings fronting on a private road
Provisions for Single and Sami Datashad Dwallings		

#### **Provisions for Single and Semi-Detached Dwellings**

Subject to same provisions as the proposed R1B.AAA Zone, except maximum height shall be 3 storeys

#### **Provisions for Back-to-back townhouses**

Subject to same provisions as the proposed R4.CCC Zone

### Provisions for Street Townhouses, Group Townhouses (with Parking/Garage adjacent frontage)

Subject to same provisions as the proposed R4.BBB Zone

<b>Provisions for Str</b>	reet Townhouses, Group Townhouses (with Parking	/Garage accessed via Rear Lane)
Min. Lot Area	Interior Lot: 156 m2; or 163 m2 with parking access via rear lane	Interior or End lot - 100 m2 per unit Corner lot – 140 m2 per unit
	Corner lot: 215 m2 (with attached garage); or 192 m2 (with parking access via rear lane)	
Min. Lot Frontage	Interior Lot: 5.5 m or 6.0 m per unit (with parking accessed via a rear lane  Corner lot: 8.0 m or 7.5 m per unit (with parking accessed via a rear lane)	Interior lot – 4.5 metres per unit End Lot – 5.0 metres per unit Corner lot – 6.0 metres per unit
Min. Front yard	3.0 m (where a detached private garage or parking space is accessed via a rear lane)	NO CHANGE  - The yard adjacent the main entrance of dwelling shall be deemed the front yard.
Min. exterior side yard	3.0 metres	2.4 metres except that an attached garage fronting on flankage street shall be 6.0 metres from the lot line on the flankage street
Min. Interior Side yard	1.2 m and 0.0 m along common wall 2.0 m between Group Townhouses	NO CHANGE
Min. Rear Yard	7.5 m 13.5 m (with parking accessed via a rear lane)	<ul><li>6.0 metres to garage face.</li><li>The yard adjacent the garage shall be deemed the rear yard.</li></ul>
Max. Building Height (m)	11 m	3 storeys
Min. GFA	65 m2	NO CHANGE
Min. Landscaped Open Space -	30 %	NO CHANGE

required front yard		
Provisions for Sta	acked Townhouses	
Min. Lot Area	Interior Lot – 120 sq. m. per block Corner Lot – 120 sq. m. per block	NO CHANGE
Min. Lot Frontage	Interior Lot – 8 m. per block Corner Lot – 8 m. per block	NO CHANGE
Min. Front yard	6.0 m.	4.5 m.
Min. exterior side yard	3.0 metres	2.4 metres except that an attached garage fronting on flankage street shall be 6.0 metres from the lot line on the flankage street
Min. Interior Side yard	2.0 m.	NO CHANGE
Min. Rear Yard	7.5 m 13.5 m (with parking accessed via a rear lane)	6.0 metres
Max. Building Height (m)	11.0 m	3 storeys
Min. GFA Min. Landscaped Open Space - required front yard	65 m2 20 %	NO CHANGE NO CHANGE
	Definition of Street Townhouse	
	"DWELLING, STREET TOWNHOUSE" shall mean a dwelling containing three or more dwelling units with each dwelling unit being divided one from the other by an above grade vertical common wall, and with each dwelling unit fronting onto a street	Notwithstanding the definition of Dwelling, Street Townhouse, the following shall apply: Townhouses shall mean a dwelling house comprising three or more dwelling units with each dwelling unit being divided one from the other by an above grade vertical common wall, a minimum of 10 square metres in area and each dwelling unit having direct access to a yard. A maximum of eight dwelling units are permitted in a row.
	<b>4.2 Accessory Buildings in Residential Zones</b> No building, or structure which is accessory to any	NO CHANGE
	permitted residential use in any zone shall:  a) be established on any lot until or unless the main building or use to which it is accessory is established; b) exceed a building height of 4.5 metres in the Residential Zones and 6.5 metres in all other zones where the use is permitted;	NO OHANGE

- c) occupy any part of a required exterior side yard or required front yard;
- d) be nearer than 1.0 metres of a lot line within an interior side yard or 1.0 metres of an interior lot line within a front yard;
- e) be nearer than 1.0 metre of an interior lot line within a rear yard except:
- i) in the case of a mutual private garage or a mutual boathouse in the rear yard on a common interior side lot line, no setback is required,
- ii) in the case of a lot line abutting a navigable watercourse, no setback is required for a boathouse, dock, pier or wharf where the boathouse, dock, pier or wharf abuts the watercourse:
- f) occupy more than 10% of the lot area to a maximum of 75 square metres of useable floor area, whichever is lesser, for all accessory buildings or structures together, in the R1, R2, R3, R4, RL residential Zones; 100 square metres of building area on those lots measuring 0.4 hectares or less in all other zones where the use is permitted, and 200 square metres of building area on those lots measuring 0.4 hectares or more in all other zones where the use is permitted. Swimming pools shall not constitute a structure for the purposes of this provision:

#### Provision

#### Section 4.15 – Decks and Unenclosed Porches

(a)

- i) A deck or unenclosed porch having a maximum height of 0.3 m above finished grade or less shall be permitted to encroach into any required yard setback without restriction, provided it is located:
- no closer than 1.0 m to the rear or interior side lot line and
- no closer than 1.5 m to the front or exterior side lot line;
- ii) A deck or unenclosed porch having a maximum height greater than 0.3 m above finished grade shall be permitted to encroach up to 2.0 m into the required rear yard or required exterior side yard, provided it is located no closer than 2.0 m from the exterior or rear lot line. For interior side yards, it may not encroach further than the required side yard setback. For the front yard, the deck may encroach no greater than 1.5 metres.
- iii) No deck shall have a floor higher than the height of the floor of the first storey of the main dwelling on the lot. Anything constructed above the first storey shall be considered a balcony and is regulated under Section 4.20 of this By-law; and
- iv) A deck or unenclosed porch on a sloping rear yard shall be no closer than 1.5 metres from an interior lot line and 5 metres from the rear lot line,

That notwithstanding Section 4.15, a porch may project into any required front yard setback a distance of not more than 2.0 metres; any required exterior side yard setback a distance of not more than 1.8 metres; and, any required rear yard setback a distance of not more than 2.5 metres.

That notwithstanding Section 4.15, a patio or deck above the finished grade may project into any required rear yard setback a distance of not more than 2.5 metres. Any patio or deck constructed in a rear yard is restricted to a maximum size of 3.1 metres by 2.5 metres. (Not applicable to Townhouses with parking accessed via rear lane)

(b)	at the point where the deck floor reaches or exceeds a height of 2 metres above the finished surface of the ground.  Notwithstanding the above, where the rear lot line adjoins a water body or watercourse, a deck or unenclosed porch may project to the limits of any natural hazard land or top-of-bank setback.	
Provision	Section 4.20 - Other Exceptions from Yard Provisions	
(a)	sills,belt courses, cornices, chimneys, bay windows, pilasters, hydro meters or gas metres may project into any required yard or setbackarea a distance of not more than 0.65 metres;	NO CHANGE
(b)	eaves or gutters for other than an accessory building may project into any required yard or setback area a distance of not more than 0.65 metres	NO CHANGE
(c)	eaves or gutters of an accessory building may project into any required yard or setback area a distance of not more than 0.3 metres	NO CHANGE
(d)	canopies, awnings, or steps may project into any required rear yard, front yard or exterior side yard area a distance of not more than 1.5 metres	NO CHANGE
(e)	balconies may project into any required rear yard, front yard, interior side yard or exterior side yard area a distance of not more than 1.5 metres provided they are no closer than 3.0 metres from a front yard lot line, exterior lot line or interior lot line and 6.0 metres from a rear lot line;	For Street/Group Townhouses with parking accessed via a rear lane, a balcony may project into a rear yard a distance of not more than 3.5 metres.  For Stacked Townhouses, a balcony may project a distance of not more than 2.5 metres into the front yard and 2.5 metres into the rear yard.
(f)	unenclosed accessibility ramps may project into any required yard;	NO CHANGE
(g)	window or wall-mounted furnaces, heat pumps, gas fireplace vents and outdoor free-standing air conditioning units may project into any required rear yard, interior side yard, or exterior side yard a distance of not more than 1.0 metres and provided it is no closer than 6.0 m to a rear lot line or 1.5 m to an interior or exterior lot line;	That an air conditioning unit shall be setback a minimum of 0.6 metres from any side or rear property line. An air conditioning unit is not permitted in any part of a required front yard or front setback.
(h)	steps including landings, above or below grade entrances and staircases may project into any required rear yard, front yard, interior side yard or exterior side yard area a distance of not more than 1.5 metres; and into the front yard not more than 2.0 metres.	Steps/stairs may project into any required front yard or setback a distance of not more than 3.5 metres.

	(i)	a stair encroachment of 3 risers, to a maximum of	Not Applicable
	•	0.6 metres, may be permitted.	
Provision		Section 3 Definition, Section 4.56, Table 4.56 - Sight or Daylight Triangles	R4 Zone Exception
	(a)	Any building, structure, sign or use which would obstruct or impair the vision of a vehicle operator, or any fence or vegetation exceeding 1.0 metres in height above finished gradeshall be prohibited within any sight (or daylight) triangle. This provision shall not apply to field crops or a wire farm fence.  A sight (or daylight) triangle shall be measured	a) Intersections of Local Roads "SIGHT TRIANGLE" shall mean the triangular space formed by the intersecting street lines of a corner lot and a line drawn from a point on one of the street lines to a point on the other street line, each point being measured 4.5 metres from the point of intersection of the street
	(b)	back from the point of any at-grade intersection of two or more street lines on a corner lot and a railway right-of-way in accordance with the street classification as identified on Schedule F of the CountyOfficial Plan and Table 4.56:  Table 4.56: Minimum Sight (or Daylight) Triangle Requirements  Street Classification Intersecting Street Minimum Sight Triangle	lines. b) Intersections of Local Road / Collector Street "SIGHT TRIANGLE" shall mean the triangular space formed by the
		Classification	intersecting street lines of a corner lot and a line drawn from a point on one of the street lines to a point on the other street line, each point being measured 7.5 metres from the point of intersection of the street lines.
	(c)	The values in Table 4.56 shall be considered the minimum and a Transportation Study and Traffic Functional Design Study shall be required by the County in order to help determine the roadway requirements	c) That front yard, side yard and rear yard setbacks shall be measured as if the Sight Triangle does not exist.
Provision		Section 5.2.3 – Parking Space Dimensions	
	(a)	Every parking space shall be based upon a rectangular shape having a width of 3.0 metres and a depth of 5.8 metres.	The parking space size located within a garage shall have a minimum width of 3.0 metres and have a minimum length of 6.0 metres. Stairs, to a
	(b)	Notwithstanding anything to the contrary, where the length of a parking space is located adjacent to a wall or fence said parking space shall have a width of 3.3 metres and a depth of 5.8 metres.	maximum of 3 risers or 0.61 metres, shall be permitted to encroach into this parking space.
	(c)	A parallel parking spaces shall have a width of 2.7 metres and a depth of 6.5 metres.	
	(d)	Angled parking spaces shall be based upon a rectangular shape in accordance with subsection 5.2.3 a).	
	(e)	A tandem parking space shall have a width of 3.0 metres and a minimum length of 11 metres.	